JOINS CHART 11424 (west) · JOINS CHART 11429 (south) · CONTINUED ON MAIN CHART (Punta Gorda)

THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES

FLORIDA - GULF COAST

ESTERO BAY TO LEMON BAY

INCLUDING CHARLOTTE HARBOR

Mercator Projection
Scale 1:80,000 at Lat. 26°36'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

HEIGHTS

Heights in feet above Mean High Water.

Additional information can be obtained at nauticalcharts.noaa.gov.

TIDAL INFORMATION

PLACE NAME	(LAT/LONG)	Height referred to datum of soundings (MLLW) Mean Higher High Water (feet)	Mean High Water (feet)	Mean Low Water (feet)
Port Ybel	(26°27'N/82°01'W)	2.6	2.3	0.5
Port Boca Grande	(26°43'N/82°15'W)	1.6	1.3	0.4
Punta Gorda	(26°56'N/82°04'W)	1.9	1.5	0.3

Datnes (– – –) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov. (Sep 2015)

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 5 for important supplemental information.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers and U.S. Coast Guard.

NOTE S

Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.260" northward and 0.679" eastward to agree with this chart.

NOTE N

The channel is marked by private daybeacons numbered "2" thru "16". The controlling depth was 2 feet in 1981.

NOTE P

Many of the tributaries of Peace River are marked by private aids.

SCALE 1:80,000
Nautical Miles 1 ½ 0 1 2 3 4 5 6
Yards 1000 0 2000 4000 6000 8000 10000

For Symbols and Abbreviations see Chart No. 1

COLREGS: International Regulations for Preventing Collisions at Sea, 1972. Demarcation lines are shown thus: – – – –

ACKNOWLEDGMENT

The National Ocean Service acknowledges the exceptional cooperation received from members of the Peace River Power Squadron, District 22, United States Power Squadrons, in continually providing essential information for revising this chart.

NOTE X

Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation, some Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the other laws. The 9-nautical mile Natural Resource Boundary off the Gulf coast of Florida, Texas, and Puerto Rico, and the Three Nautical Mile Line elsewhere remain in most cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical mile Exclusive Economic Zone were established by Presidential Proclamation. Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject to modification.

HURRICANES AND TROPICAL STORMS

Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.

Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charted positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area — — — — — — Cable Area

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.

Covered wells may be marked by lighted or unlighted buoys.

CAUTION

Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.

Radio-direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

Station positions are shown thus:
⊙(Accurate location) o(Approximate location)

NOTE L
BRIDGE INFORMATION

(A) SWING BRIDGE HOR CL 80 FT VERT CL 22 FT
(B) FIXED BRIDGE HOR CL 120 FT VERT CL 26 FT (AT CENTER) OVHD PWR CAB AUTH CL 35 FT
(C) FIXED BRIDGE HOR CL 40 FT VERT CL 14 FT (AT CENTER) OVHD PWR CAB AUTH CL 27 FT

NOTE E
Jug Creek channel is marked by private markers.

NOTE O
The daybeacons are private and positions are approximate.

NOTE J
Hydrography and shorelines in this area are subject to continual changes.

NOTE B
INTRACOASTAL WATERWAY
(Charts 11425, 11427)

The project depth is 9 feet from Caloosahatchee River to the Anclote River, FL.

Consult the U.S. Army Corps of Engineers for controlling depths and U.S. Coast Guard Local Notice to Mariners for other navigation hazards or restrictions.

NOTE C

Strong cross currents are encountered especially during ebb of spring tide between daybeacons "2A" and "8".

NOTE F

The channel is marked by private daybeacons. The controlling depth was 6 feet. Feb 2014

NOTE H

The channel is subject to frequent changes. Channel marked by private aids.

NOTE K

The natural channel location through Stump Pass is subject to continuous change in alignment and depth. DO NOT NAVIGATE in or through the area without absolute knowledge of channel location and depth. The channel is marked by private aids.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION

BASCULE BRIDGE CLEARANCES

For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 5. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 7th Coast Guard District in Miami, Florida, or at the Office of the District Engineer, Corps of Engineers in Jacksonville, Florida.

Refer to charted regulation section numbers.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Fort Myers, FL	WXK-83	162.475 MHz
Sarasota, FL	WWG-59	162.40 MHz
Naples, FL	WWG-92	162.525 MHz

NOTE Q

The daybeacons are private and positions are approximate.

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE

B2	1970 - 1989	NOS Surveys partial bottom coverage
B3	1940 - 1969	NOS Surveys partial bottom coverage
B4	1900 - 1939	NOS Surveys partial bottom coverage
B5	1834 - 1899	NOS Surveys partial bottom coverage

CONTINUATION OF PEACE RIVER

Scale 1:40,000 at Lat. 26°36'

Nautical Miles ½ 0 1
Yards 1000 0 1000 2000 3000

NOTE D
ANCHORAGE AREA
166.200
(see note A)

Dump Site (discontinued) (dredged material) (see note S)
20 ft rep 1984
Depths from survey of 1981

SAFETY FAIRWAY 166.200 (see note A)

COLREGS DEMARCATION LINE 80.750E (see note A)

TERRITORIAL SEA (see note X)

NATURAL RESOURCES BOUNDARY (see note X)

THREE NAUTICAL MILE LINE (see note X)

CONTINUED ON MAIN CHART

11426

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

This is the Last Edition of this chart. It will be canceled on Apr 3, 2024

40th Ed., Apr. 2019. Last Correction: 2/16/2024. Cleared through:
LNM: 1224 (3/19/2024), NM: 1324 (3/30/2024).

To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).
If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm.

SOUNDINGS IN FEET

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

(POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations, including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod

FATHOMS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
FEET 6 12 18 24 30 36 42 48 54 60 66 72 78 84 90 96 102
METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

Estero Bay to Lemon Bay
SOUNDINGS IN FEET-SCALE 1:80,000

11426

1142.7 X 787.1 mm